

DEGA PRIMER

Insulating anti-dust resin.

DESCRIPTION: DEGA PRIMER is a synthetic chemical product in form emulsified with particular property of penetration to the support and the plaster, to consolidate any friable part.

It relatively constitutes a plastic, transparent, water-repellent, anti-damp and anti-dust film.

EMPLOYMENTS: DEGA PRIMER is employed for the treatment of consolidation and waterproofing of supports and coverings both insides both external, in cement, plaster, wood, drywall, and preventively to the treatment, what insulating anchoring with products of the line Dega specifies.

APPLICATION: To directly apply on the surface preventively polished up, using brush, roll or to spray.

TECNHNICAL DETAILS:

Temperature limit of exercise	- 30°C. + 80°C.
Least temperature of application	+ 5° C.
Time of use of the product	boundless
Desiccation at 20°C.	2-3 hours about
Specific weight	about 1,200 Kilos/dmc.
Consumption	0.2 lt/sqm in operation of the absorption of the support
Storage time	about 12 months at 20°C – fears frost.
Packagings	lt. 1 – lt. 5 – lt. 10

The values indicated mean tests averages. What indicated about the method of use and the results obtainable with our product correspond to our experiences, without however constituting our use and responsibility. Therefore, the sale of our product is not covered by guarantee with regard of application and is carried out with the understanding that the user will determine the suitability.

Certificato:



UNI 8298

Gobetto srl - Via Carroccio, 16 - 20123 Milano, Italy
tel. +39 02 8322269 fax +39 02 89404269
gobetto@gobetto.com www.gobetto.com

C.C.I.A.A Milano n. 991513
Iscriz. n. 182471 Trib. di Milano
C.F. e Part. Iva 04018090151