

DEGA STABIL

DESCRIPTION: **Dega Stabil** is an organic chemical epoxy emulsion, particularly studied for the impregnation and consolidation of powdery and beachy grounds. The product is non-toxic and fireproof.

USE: **Dega Stabil** is used for the consolidation of supports and coatings, both indoor and outdoor, made of concrete, or as protective finishing of the Dega Carpet cycle.

APPLICATION: Apply directly on the surface with a roll or a brush.

TECHNICAL DATA:

Limit temperature of exercise	-10°C. + 50°C
Minimum temperature of exercise	10°C
Drying at 20°C	about 4h
Specific weight	About 1090Kg/dmc
Consumption	0.3-0.5 kg/mq
Packaging	25Kg

The values indicated mean tests averages. What indicated about the method of use and the results obtainable with our product correspond to our experiences, without however constituting our use and responsibility. Therefore, the sale of our product is not covered by guarantee with regard of application and is carried out with the understanding that the user will determine the suitability.

Certificato:



UNI 8298

Gobetto srl - Via Carroccio, 16 - 20123 Milano, Italy
tel. +39 02 8322269 fax +39 02 89404269
gobetto@gobetto.com www.gobetto.com

C.C.I.A.A Milano n. 991513
Iscriz. n. 182471 Trib. di Milano
C.F. e Part. Iva 04018090151