

KRISTAL STUCCO

Mono-component fine resin stucco.

DESCRIPTION: KRISTAL STUCCO is a paste product, without solvents (nontoxic), monocomponent of synthetic modified copolymeric base resins, loaded with pigments, loaded lamellar and quartzifer fibrous elements. It is a tixotropic product and therefore it can also be used for vertical applications. It gives to the surface a plain and smooth look.

USE: the product, available in different colors, is used for the final shaving, also in vertical applications. It doesn't damage the polystyrene.

PREPARATION OF THE EXISTING GROUND: the surface of application must result cleaning up and dry. Specific preparations will be valued according to the existing ground. To sanding and to apply a hand of Dega Plast Primer before laying KRISTAL STUCCO.

APPLICATION: previously apply a hand of Dega Plast Primer and let dry. Subsequently apply KRISTAL STUCCO in a millimetric trimming, through the use of a smooth spatula.

Once the applied layer is dry, we will proceed with a further fine trimming of KRISTAL STUCCO, removing smears or superficial incongruities.

Once hardened, it must be subsequently refined with sanding. To this point, a planar and smooth surface is obtained.

To obtain thicknesses of 2-3 mm, it's advisable to apply a first hand of Dega Plast Stucco and two trimmings of KRISTAL STUCCO.

It's possible to aesthetically refine the surface with various decorations. The protective finishing can be done using Dega Gamma Eco/TR, Dega Brek, Gel Coat or Poliepo.

KRISTAL STUCCO

TECHNICAL DATA:

Temperature limit of exercise	- 30°C + 60°C
Least temperature of application	+ 5° C
Time of working	operating in environment temperature about 30'
Desiccation at 20° C	out dust: 30'; dry: in operation of the applied thickness, es: for 2 mm. about 4 h
Hardening	About 4 hours
Specific weight	1,6 Kg./Lt.
Surrender	tightly depending on the type of intervention effected on the support. For trimming: middle consumption of about Kg.1-1,2 for 1 mm / sqm
Time of stocking	About 12 months – Note: it is not coldproof
Wrappings	1 Kg. – 3 Kg. – 10 kg - 25 kg

2/2

The values indicated mean tests averages. What indicated about the method of use and the results obtainable with our product correspond to our experiences, without however constituting our use and responsibility. Therefore, the sale of our product is not covered by guarantee with regard of application and is carried out with the understanding that the user will determine the suitability.

Certificato:



UNI 8298

Gobbetto srl - Via Carroccio, 16 - 20123 Milano, Italy
tel. +39 02 8322269 fax +39 02 89404269
gobbetto@gobbetto.com www.gobbetto.com

C.C.I.A.A Milano n. 991513
Iscriz. n. 182471 Trib. di Milano
C.F. e Part. Iva 04018090151