

## STREET SPOT By Gobbetto

### Walking in advertising

**DESCRIPTION:** advertising resin coating based in the application of advertising posters and spots coated by special transparent resins of the DEGA- MONOSINT® line, solvent-free, anti-slippery and class 1 fireproof.

**STREET SPOT** is applicable on surfaces of different nature, and is easily removable thanks to a special detaching primer which assures good adherence and at the same time, when being submitted to steam or hot air at 100°C, it can be removed without leaving residues and without ruining the existing ground.

**USE:** coat sidewalks, pedestrian ways, exterior floorings, tiles etc. with removable advertising. Street Spot is a walkable and removable surface, particularly indicated for temporary advertising posters and spots.

### APPLICATION:

#### OUR KNOW HOW IN THE PATENTED STREET SPOT

Clean and degrease the surface to be coated. Pour a special detaching resin primer, fix a special paper or textile with Dega Stabil resin. Lay a protective finishing with anti-slippery Gel Coat.

**REMOVAL:** To remove Street Spot it's sufficient to weaken one of the exterior edges by heating and remove with the possible help of steam, hot water or hot air. Clean the previously coated surface with AP/10 or AP/98, removing any residue in order to bring the surface to its original status, integral and intact.

### TECHNICAL DATA:

|  |                               |
|--|-------------------------------|
| Limit temperature of exercise                                | -12°C, + 60°C                 |
| Application temperature                                      | + 6°C, +35°C                  |
| Time of use after the mixture of the two components at +20°C | About 1h                      |
| Drying   | 4-8h depending on temperature |
| Total hardening  | About 8-12h                   |
| Dosing depending on capitulated                              |                               |
| Application  | Roll, spray, brush            |
| Render for each hand depending on capitulated                |                               |
| Stocking time at 20°C  | About 12 months               |

The values indicated mean tests averages. What indicated about the method of use and the results obtainable with our product correspond to our experiences, without however constituting our use and responsibility. Therefore, the sale of our product is not covered by guarantee with regard of application and is carried out with the understanding that the user will determine the suitability.

Certificato:



UNI 8298

**Gobbetto srl** - Via Carroccio, 16 - 20123 Milano, Italy  
tel. +39 02 8322269 fax +39 02 89404269  
[gobbetto@gobbetto.com](mailto:gobbetto@gobbetto.com) [www.gobbetto.com](http://www.gobbetto.com)

C.C.I.A.A Milano n. 991513  
Iscriz. n. 182471 Trib. di Milano  
C.F. e Part. Iva 04018090151