

DEGA ALFA (A+B)

Transparent, two-component resin treatment.

DESCRIPTION: modified synthetic two-component resin, transparent and solvent-free, excellent resistance to scratching, wear and water. Available in shiny or satin effects.

USES: protect and cover different surfaces. Excellent for the protection of DEGA line floors. Suitable for homes, shops, exhibition spaces, etc.

Also indicated for outdoor surfaces or in contact with water; such as terraces, swimming pools, showers, etc.

APPLICATION: Mixing ratio is 1 to 0.4 (ex. 1000gr part A; 400gr part B). Mix before use, apply with a paint roller, brush or spray.

It is advisable to apply 1/2 and wait at least 2-3 h between the 1st and the 2nd layers.

TECHNICAL DETAILS:

Temperature limit of exercise	- 10° C. + 70°C.
Least temperature of application	+15° C.
Out of dust	2 h at 20°C
Complete hardening	24 h at 20°C
Specific weight	0,9 Kg./dmc. about
Colour	transparent
Application	brush, roll or by spray
Surrender for hand	100-150gr/sqm. due to the porosity of the support.
Stocking	12 months about.
Wrappings	Kit of Kg. 1,4 Kit of Kg. 7 Kit of Kg. 14
Mixing ratio	1÷0,4

The values indicated mean tests averages. What indicated about the method of use and the results obtainable with our product correspond to our experiences, without however constituting our use and responsibility. Therefore, the sale of our product is not covered by guarantee with regard of application and is carried out with the understanding that the user will determine the suitability.

Certificato:



UNI 8298

Gobetto srl - Via Carroccio, 16 - 20123 Milano, Italy
tel. +39 02 8322269 fax +39 02 89404269
gobetto@gobetto.com www.gobetto.com

C.C.I.A.A Milano n. 991513
Iscriz. n. 182471 Trib. di Milano
C.F. e Part. Iva 04018090151